Conclusions of the 5th European American Workshop on Reliability of NDE

Christina Müller, Ralf Holstein, Marija Bertovic, Berlin, Germany

Article Information

Correspondence Address

Christina Müller Fachbereich 8.3, Bundesanstalt für Materialforschung und -prüfung Unter den Eichen 87, 12205 Berlin, Germany E-mail: Christina.Mueller@bam.de

Keywords

NDE reliability, POD, Bayesian approach, structural health monitoring, human factors, open space technology

The insights from the first four workshops from the series of "European-American Workshops on Non-Destructive Evaluation (NDE) Reliability" can be summarized as follows. The main achievement from the first workshop 1997 in Berlin - in a time of debating whether testing according to standards, i.e., well defined parameters or qualification by blind trials would yield the right quality - was the conceptual model [1] (later referred to as modular reliability model [2]) in terms of the reliability formula. According to this model, the total reliability of an NDE system is composed of the intrinsic capability, IC (physical principle behind the defect indication and its technical realization as an upper bound), the application factors, AP (realistic circumstances such as the UT coupling, limited access, noise of the surrounding, etc.) and the human factors, HF, present in each application. While imperfect - e.g., the mutual interactions between the factors were not considered - the conceptual model helped to properly define the potential for performance optimization, and worked as an assessment tool for the adequacy of open and blind trials. The main benefit from the Second European American Workshop on NDE Reliability, September 1999, Boulder, Colorado, USA [3], was the clear definition

The tradition of discussing the newest achievements in the consideration of NDE reliability was continued with the 5th European American Workshop on Reliability of NDE (5th EAW) in Berlin in 2013. The focus of this workshop was to determine the "delta" between the laboratorylike conditions, in which reliability assessments are usually carried out, and the everyday field conditions. Which obstacles need to be still overcome and how do we get closer with our estimations to the real field reliability? With the joint effort of international researchers and in-field practitioners the up-to-date research was presented and discussed, culminating in a half-a-day long "Open Space Technology" discussion. This paper presents the main conclusions of the workshop.

of i) the NDE system as the procedure, equipment and personnel, that are used in performing an NDE inspection and ii) the NDE reliability as the degree that an NDT system is capable of achieving its purpose regarding detection, characterization and false calls. The main conclusion from 2002 from the third European American Workshop [4] was: We need to quantify the risk in NDE and demining. The fourth European American Workshop in 2009 in Berlin again showed the progress in attempts to consider the reliability of NDE on a system level with the goal for integrated solutions in the industrial applications. The limitations of the original empirical methods were shown resorting to advanced and model assisted methods. Also, for the first time an extra human factors session was launched resulting in the recognition that human factors are present in all stages of an NDE activity. Potential for improvement is seen in the training, procedure, calibration, inspection, and data evaluation.

In the year 2013, the overall question to be answered remained: What is influencing the performance of NDE and how can we measure and optimize what we want to know with minimum effort? The focus of the current workshop was: What is the "delta" to the everyday field conditions? What do we need to overcome?

In the 37 oral presentations and 25 posters different general strategies and specific solutions from the scientific and industrial point of view were already presented. However, the highlight of the 2013 event was the "Open Space Technology" (OST) workshop. The "Open Space" format was selected to replace the "break-out-sessions" format from the former workshops, in which a specific goal for each working group was defined beforehand. The underlying principle of an OST workshop, developed by Owen in the sixties, and ideal for large groups, is to allow the people to work on a topic that interests them [5, 6]. It works on a principle that offers participants complete freedom in the choice of the topic, the duration, the participants and the flow of the discussion: and resides on a "law of two feet", which allows the participants to move from one discussion point to another and to leave the discussion, if it no longer pleases them.

In the preparation of the Open Space Technology discussion to be held on the last day of the workshop, every participant had the possibility to place questions or urgent issues on a wall of ideas. This was frequently used and on the morning of the discussion the board was full. In the open forum six groups of interest were formed based on the questions on the wall. The groups separated and, under the lead of an expert, i.e., the group leader, the different issues have been discussed. At the end of the day the groups recollected and presented the content and the result of their work. Every group leader wrote a summary of the discussion, which is available in another contribution in this journal issue under the title "Summary of the Open Space Technology Discussions" [7]. Here is a short summary of the most important discussion conclusions.

Summary of the Most Important Conclusions from the Discussion Groups

Group A: "New Reliability Methods: Multiparameter POD, MAPOD, Bayesian". The focus of this group discussion was how to combine the data from different sources properly, weighted for quality or importance, for instance using the Bayesian update method.

This leads to a few key choices for the engineer or scientist responsible:

- 1. What data shall serve as the prior?
- 2. How will the new data be weighted?
- 3. Will the new data be checked for consistency with the original assumptions?

A key outcome of the discussion was the suggestion that an application guide including working problems would be a great benefit. This is a potential subject for the next workshop to undertake" (quotation from Group A summary report by David Forsyth & Pierre Calmon):

Group B: Reliability of Structural Health Monitoring. The main discussion areas were:

- 1. The ways in which structural health monitoring (SHM) is different from conventional non-destructive evaluation (NDE)
- 2. Reliability issues of SHM systems
- Issues concerning determination of reliability of SHM (quotation from the Group B summary report by Jay Fisher).
 Group CDE (union of applications in industry, human factors, integrated solution and "delta" topics). This most complex field of reliability and human factors application in industry treated a number of different questions:
- What POD is good enough? The necessary POD should be decided jointly between the structural integrity and NDT groups - this was the general consensus of the group. A higher POD value causes higher cost in demonstration and implementation (quoted from summary report by Luke Carter).

- 2. Definition of requirements of NDE reliability by customer versus provider: The group discussed the question of the definition of requirements on NDE from the customer's (end user) point of view in contrast to the requirements seen from the NDE research and provider's point of view. A gap was discovered between both positions and means to overcome discussed. Bridging gap between both positions could be found in an agreement on reasonable targets. This requires in its turn an adequate information management between both parties (quoted from CDE summary report by Christina Müller).
- 3. Human factors: It appears that there is a lot of interest in the influence of human factors on the reliability of NDE, at least from the research community. However, there is a gap in the communication between the utilities and the service providers causing problems in the transfer of knowledge and, hence, posing a difficulty to implement the findings in the field. The following conclusions for future work were drawn: A broad discussion and raising of awareness is needed between the customer and the NDT service providers. Considering that the customer is no NDE expert, it is up to the NDE community to spread the word. However, the customer should take over the responsibility and consider the benefits and the costs of considering NDE reliability and human factors (quoted from CDE summary report by Marija Bertovic & Luke Carter).
- 4. How do we keep an inspector vigilant, even when they never see a flaw? Requalification to refresh operator knowledge and skills for detection and characterization, recording geometric indications to keep operators occupied during their task, yearly practice on test components with realistic defects, engagement with staff in non-outage time (developing procedures, performing open trials) were some of the suggested solutions for the vigilance problem (quoted from CDE summary report by Marija Bertovic & Luke Carter).

What advantages and disadvantages regarding the reliability can be foreseen in automated, mechanized vs. manual inspection? In general, it was concluded that the reliability is higher in mechanized inspection compared to manual inspection, but it was stated that the mechanical system is not always as good as the best manual inspector but at least better than the average manual inspector. In general, it needs to be spread out that there are still needs to investigate the reliability of more or less automated inspection systems. Especially as it has been concluded that the errors that might occur often are different from errors in manual inspection. One of the most important tasks in mechanized inspection is the evaluation of data and as it often includes interpretation of complex signals and/or images, there is a need for high quality procedures (quoted from CDE summary report by Ulf Ronneteg).

Group F: Basic Concepts of Reliability of NDE. Even if the NDE reliability has gone a long way, there is still a need to discuss the fundamental principles that form the basis for all advanced concepts. The topics discussed ranged from confidence bands, applicability of POD to different kind of defects and sensors, the role of thresholds up to the connection of POD to risk analysis. From the wide spectrum of questions it can be concluded that there is a need for learning materials in form of the text book and possibly organization of courses and tutorials on the topic of reliability of NDE (quotation from the Group B summary report by Mato Pavlovic & Ward Rummel).

What Can be Concluded in Total from the Presentations and the Open Space Technology Workshop?

Reliability of NDT is an active scientific field which is interesting for many users of NDE, as shown by a large number of participants, even on the 5th workshop of this kind.

The newcomers were interested to learn more about the basic ideas of reliability in NDT. This raised the question of why there is not enough learning material and sample data on the market.

The "insiders" of reliability of NDE were in the process to search for the "delta" between the output of our current reliability models and the actual reliability in the field.

In this context, human factors seem to be a field where further knowledge is needed. The transfer of knowledge of the optimal working conditions for operators and the optimal organizational environment from theory into praxis, to guarantee an adequate information process (which means the flow of information followed by mutual feedback and common understanding) for all involved parties, is a key point.

It also became apparent that the information exchange about the target of testing and the reliability from the NDE and structural integrity point of view is necessary between the end user and the NDE service provider.

The use of mechanized or automated NDT systems does not completely remove human influence. Even though by introducing mechanized/automated NDE many of the errors, which occur during the manual NDE, can be avoided, new errors can arise. Therefore, even here the influencing factors and processes (especially in the case of evaluation of data) must be taken into account.

A lot of progress has been made during the last years in using different mathematical models for the handling of POD data and making the POD affordable or even possible. Still, there is much more knowledge necessary about the validity of these models and their correct use. To overcome the high costs of a statistically sufficient number of artificial and natural specimen modeling is more and more used. Further investigation is required to improve the validity of these models.

The final topic discussed was if the reliability approach for the traditional NDE can be directly transferred to structural health monitoring. It was concluded that a direct transfer is not possible since both systems work under very different conditions and approaches. There is a need to understand the difference and to develop own models for SHM reliability.

The huge amount of open questions concerning reliability of NDE on the one hand, and the limited resources for research and development in this field on the other hand, motivated the participants of the workshop to gain the advantage of mutual support and information from the series of "European American Workshops on Reliability of NDE" and to meet already after two years again in connection with the QNDE 2015 in the US. Before the accomplishment of this article it was agreed that a special session on reliability will already be organized during the QNDE 2014 devoted to the advanced methods (Group A).

References

- C. Nockemann, C. Fortunko: Summary of the workshop. Proceedings of the European American Workshop on Reliability and Validation Methods on NDE, Berlin, Germany, June 18-20 (1997)
- 2 C. Müller, M. Bertovic, M. Gaal, H. Heidt, M. Pavlovic, M. Rosenthal, K. Takahashi, J. Pitkänen, U. Ronneteg: Progress in Evaluating the Reliability of NDE, Systems -Paradigm Shift, Proceedings of the 4th European American Workshop on Reliability of NDE, Berlin, June 24-26 (2009), DGZfP Proceedings BB 116-CD

Abstract

Schlussfolgerungen des 5. Europäisch-Amerikanischen Workshops zu Zuverlässigkeit in der ZfP. Die Diskussion der neuesten Erkenntnisse zur Zuverlässigkeit in der ZfP, wurden auf dem 5. Europäisch-Amerikanischen Workshop 2013 in Berlin traditionell fortgesetzt. Besonderes Augenmerk galt dabei, die Unterschiede zwischen unter Laborbedingungen durchgeführten Zuverlässigkeitsuntersuchungen und den tatsächlichen vor-Ort-Bedingungen zu untersuchen. Im Mittelpunkt der Diskussionen stand die Frage, welche Schwierigkeiten überwunden werden müssen, um bei den Zuverlässigkeitsanalysen die realen Bedingungen näher erfassen zu können. Gemeinsam haben Wissenschaftler und Praktiker den aktuellen Stand der Forschung in einer halbtägigen Open Space Diskussion besprochen. In diesem Beitrag werden die wesentlichen Schlussfolgerungen des Workshops zusammengefasst.

- 3 ASNT Topical Conference Paper Summaries Book of the American European Workshop on Non-Destructive Inspection Reliability, September 21-24 (1999), NIST, Boulder, CO, USA, ISBN: 1 57117 041 3
- 4 R. Singh, M. Anderson, C. Müller: Summary & Consensus, Breakout session 5, Proceedings of the 3rd European American Workshop on Reliability of NDE and Demining, DGZfP Proceedings BB-81-CD (2002)
- 5 R. Seliger: Einführung in Großgruppen-Methoden, Heidelberg: Carl-Auer Verlag (2011)
- 6 O. Harrison: Open Space Technology:
- Ein Leitfaden für die Praxis, Schäffer-Poeschel Verlag (2011)
- 7 M. Bertovic, P. Calmon, L. Carter, J. Fisher, D. Forsyth, R. Holstein, B. McGrath, C. Müller, M. Pavlovic, U. Ronneteg, W. Rummel, F. Schubert and G. Selby: Summary of the Open Space Technology Discussions on Reliability of NDE, Materials Testing 56, Vol. 7-8 (2014), pp. 602-606 DOI:10.3139/120.110604

Bibliography

DOI 10.3139/120.110603 Materials Testing 56 (2014) 7-8, pp. 599-601 © Carl Hanser Verlag GmbH & Co. KG ISSN 0025-5300

The Authors of This Contribution

Dr. rer. nat. Christina Müller studied physics at the Technical University in Dresden, Germany and received her PhD in the field of theoretical solid state physics in 1982. After a phase of teaching and research at the university she worked in the practical development of material testing procedures in the electronic industry and in the development of ultrasonic probes for nuclear power plants in the former GDR. In 1988 she started to work at the BAM in the division for NDT in the field of signal processing, modeling and 3D data reconstruction. In international co-operation she developed basic principles

for reliability assessment of NDT and is since 1992 the head of a research group "Reliability of NDT" and extended the knowledge to the reliability of demining systems. Her research group developed a modular model investigating all possible influences on the reliability of NDT from the physics and industrial application factors up to the human factor including working psychology. The technical POD (probability of detection) was extended to multi-parameter approaches suited to complex and thick components and especially applied to the NDT processes for canisters for radioactive waste in Scandinavian nuclear waste programs. Dr. Müller initiated and organized an international workshop series "European American Workshop on Reliability of NDT" which took place with international success for four times since 1997. The special value of the workshop is the comprehensive and interdisciplinary approach.

Ralf Holstein, born 1961, completed an apprenticeship and worked as a technician in the field of telecommunications. In 1993 he obtained a degree in communication engineering from the Technical University of Dresden, Germany. In the same year he started working for the German Society for Non-Destructive Testing in Berlin, Germany, between 1993 and 1997 as head of the Personnel Certification Body, until 2003 as head of the training department. Since February 2003 he is the managing director of the DGZfP Education and Training Ltd. Since 2009 he is external PhD student on the VŠB - Technical University of Ostrava, Czech Republic. He is also elected chairmen of the DIN standardization committee "Qualification and Certification of Non-Destructive Testing Personnel".

Marija Bertovic, born 1981, obtained her diploma degree in psychology from the University of Rijeka in Croatia in 2006. Since then she has been working at the BAM Federal Institute for Materials Research and Testing in Berlin, Germany in division "Radiological Methods" in the area of "Reliability of Non-Destructive Evaluation Systems" as research scientist. In focus of her work are human factors affecting the reliability of NDT inspections. She is a doctoral candidate at the Berlin Institute of Technology (Technische Universität), Germany.